

SEMISYNTHETIC 4T 10W-40

SEMISYNTHETIC ALL-SEASON MOTOR OIL FOR FOUR-STROKE ENGINES.

SPECIFICATIONS:

SAE 10W-40 API SL JASO MA2 JASO T903:2016

DESCRIPTION:

Intended for lubricating systems of modern four-stroke engines of motorcycles, ATVs, scooters and other motor vehicles with any clutch type, and for the power equipment.

Using in water-cooled outboard engines is acceptable.

Produced of high-quality foreign mineral base oils with premium additives package.

BENEFITS:

- Has high thermal stability and excellent detergency;
- Provides high anti-wear protection within a wide load range;
- Provides effective overheat protection for the engine;
- Minimizes exhaust smoking and emissions toxicity;
- Contains modern premium additives package;
- Excellent stability of viscosity rating within the viscosity grade throughout the service life;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,0
Density at 20°C, kg/m ³	873
Viscosity index	143
Alkalinity, mg KOH/g	6,1
Flash point in open crucible, °C	215
Pour point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 1l	004878	482007024193

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.