

## YUKO SILICONE SPRAY

### BENEFITS:

- Prevents friction, squeaks, drying out, and freezing.
- Provides reliable protection for plastic, rubber, metal, and wooden surfaces.
- Ensures smooth operation of parts across a wide temperature range.
- Gives surfaces antistatic, water-, and dirt-repellent properties.
- Facilitates the assembly and disassembly of connections.

### TYPICAL CHARACTERISTICS:

Excess saturated vapor pressure of aerosol can contents at 20 °C	0.2-0.4 MPa, 2.0-4.0 kgf/cm <sup>3</sup>
Drying time at 20 (±2) °C	min, not more than 20
Mass fraction of non-volatile substances, %	not less than 20, not more than 45
Relative density at 15 °C, g/cm <sup>3</sup>	0.8
Degree of content evacuation from aerosol can, %	not less than 97

Packing	Vendor code	Barcode
Balloon tin 0.4l	025964	

### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.