SUPER SYNT 2T (FC)

SEMI-SYNTHETIC MOTOR OIL FOR TWO-STROKE ENGINES.

SPECIFICATIONS:

API TC JASO FC

DESCRIPTION:

Intended for using in two-stroke engines, garden and other air and water-cooled machinery.
Application in the road machinery is acceptable as well, especially where exhaust smoking restriction requirements exist.
YUKO Super Synt 2T Green Garden conforms to the requirements of API TC, and JASO FC.
Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

BENEFITS:

- Provides good lubricating, anti-wear, anticorrosion and detergent properties;
- Environment-friendly as it is smoke-free and biodegradable;
- Low-ash oil formula prevents carbon and lacquer formation;
- Provides improved engine cleanliness due to the content of synthetic components;
- The possibility of year-round use;
- Contains active additives package;
- Compatible with all engine sealings.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100˚C, mm²/s	8.1
Density at 20˚C, kg/m³	879
Viscosity index	135
Alkalinity, mg KOH/g	0.9
Flash point in open crucible, ˚C	90
Pour point, ˚C	-15

Packing	Vendor code	Barcode
Aerosol can 500 ml	023245	4823110403280
Tin can 1l	021593	4820070241594

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.

Produced according to TU U 23.2-31852954-035:2008 This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.

0 800 60 5555
Telephone hotline