

SUPER SYNTHETIC C3 5W-30

HC-SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 5W-30 API SN API SN Plus API CF ACEA C3

DESCRIPTION:

Synthetic base oil components and adapted innovative additives technology ensure smooth and reliable engine performance. The improved quality of YUKO SUPER SYNTHETIC SAE 5W-30 particularly results in further improved anti-wear protection and engine cleanliness, even during extended oil drain intervals.

The extreme low viscosity at low temperature combined with a reliable high temperature viscosity and low volatility assures a high fuel economy capacity. It contributes through its high fuel economy and reduction of emissions to protect the environment.

YUKO Super Synthetic SAE 5W-30 C3 has been developed primarily for application in Longlife service (WIV) engines of Volkswagen group. It is suitable as high performance low friction engine oil for use in a new sophisticated generation of engines and recommended for gasoline and diesel engines of all passenger cars operating in various conditions, including the turbocharged and direct injected versions equipped with catalyst. We are constantly improving our products. Product images and specifications on the website may vary.

CONFORMITY:

MB 229.31 MB 229.51 VW 504.00/507.00 BMW LL-04 Porsche C30 Fiat 9.55535-G1

BENEFITS:

- Extreme wear protection & excellent viscosity-temperature behaviour
- Minimal frictional loss & Very high cleaning capability
- Low volatilization loss & High oxidation and temperature stability
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties – rapid supply of all points of lubrication
- Very good operating reliability & multigrade usage
- Optimal engine cleanliness & lowest oil consumption
- High margin of performance & product stability
- Extended oil change intervals & prevents black sludge formation

TYPICAL CHARACTERISTICS:

Density at at 20°C kg/m ³	855
Flash point °C	230
Pour point °C	-39
Viscosity at 100°C mm ² /s	11,5
Viscosity Index	162
TBN mg KOH/g	6,7

Packing	Vendor code	Barcode
Canister plastic 20l	022594	
Oilbox carton polyethylene 20l	019794	
Tin can 1l	021587	
Tin can 4l	020770	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.