

## SYNTHETIC 5W-30

### SYNTHETIC HIGH-TECH MOTOR OIL.

#### SPECIFICATIONS:

SAE 5W-30    API SN    API CF    ACEA A3/B4

#### DESCRIPTION:

Intended for modern gasoline and diesel engines of passenger cars and vans from Japan and US carmakers.

Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

Provides improved safety as compared to mineral and semi-synthetic oils.

Special low-ash formula. Has an extended drain interval. Compatible with injector and multivalve engines, including turbocharged ones, with intercooler and catalyst.

#### CONFORMITY:

VW 502.00/505.00    PSA B71 2296    PSA B71 2300    MB 229.3    MB 229.5    GM-LL-B025    Renault RN0710

Renault RN0700    BMW LL-01    Porsche A40

#### BENEFITS:

- Provides a reliable engine protection under various conditions incl. extreme operating mode;
- Optimum for the use both in urban cycle and cross-country conditions;
- Due to its fluidity reduces fuel consumption;
- Significantly extends engine service life due to multipurpose additives package, with excellent low temperature, antifriction, anticorrosion, detergent and antioxidant properties;
- Maintains effectiveness for maximum long period, which allows to extend significantly oil drain intervals;
- Due to superior viscosity/temperature properties, provides safe engine start at low temperatures in winter, including the regions with harsh weather conditions in winter;
- Conforms to modern requirements of world leaders in equipment manufacture concerning oil consumption, volatility, energy saving.

#### TYPICAL CHARACTERISTICS:

|  |       |
|--|-------|
| Kinematic viscosity at 100°C, mm <sup>2</sup> /s | 11.35 |
| Density at 20°C, kg/m <sup>3</sup>               | 857   |
| Viscosity index                                  | 166   |
| TBN mg KOH/g                                     | 9.46  |
| Flash point in open crucible, °C                 | 201   |
| Pour point, °C                                   | -42   |

| Packing    | Vendor code | Barcode |
|------------|-------------|---------|
| Tin can 4l | 021599      |         |
| Tin can 1l | 021581      |         |

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.