

SYNTHETIC 5W-40

SYNTHETIC HIGH-TECH MOTOR OIL.

SPECIFICATIONS:

SAE 5W-40 API SN API CF ACEA A3/B4

DESCRIPTION:

Intended for modern gasoline and diesel engines of passenger cars and vans. Compatible with injector and multivalve engines, including turbocharged, with intercooler and catalyst.

Produced of high-quality foreign synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

Provides increased safety level as compared to mineral and semi-synthetic oils. Special low-ash formula. Has an extended drain interval.

CONFORMITY:

VW 502.00/505.00 MB 229.3, MB 229.5 PSA B71 2296 BMW LL-01 Renault RN0700, RN0710 Opel GM-LL-B025

Porsche A40 MB 226.5 Renault RN0700 RN0710

BENEFITS:

- Provides a reliable engine protection under various conditions incl. extreme operating mode;
- Optimum for the use both in urban cycle and cross-country conditions;
- Due to its fluidity reduces fuel consumption;
- Significantly extends engine service life due to multipurpose additives package content, with excellent low temperature, antifriction, anticorrosion, detergent and antioxidizing properties;
- Maintains effectiveness for maximum long period, which allows to extend significantly oil drain intervals;
- Due to superior viscosity/temperature properties provides safe engine start at low temperatures in winter, including the regions with harsh weather conditions in winter;
- Conforms to modern requirements of world leaders in equipment manufacture concerning oil consumption, volatility, energy saving.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.7
Density at 20°C, kg/m ³	855
Viscosity index	167
TBN mg KOH/g	10.2
Flash point in open crucible, °C	211
Pour point, °C	-42

Packing	Vendor code	Barcode
Canister plastic 20l	021318	4820070248395
Tin can 4l	021597	4820070241167
Tin can 1l	021583	4820070241150

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.