

## YUKO TOSOL A-40

### PREMIXED PREMIUM ENGINE COOLANT.

#### DESCRIPTION:

Premixed ready for use low freezing coolant. Developed for filling the cooling systems of all types (including aluminum): cars and trucks, buses, agricultural, construction and other specialized machinery, stationary engines.

Made of monoethylene glycol and BASF additives. Applied according to the OEM instructions.

Properties: engine cooling, protection of the cooling system against freezing, overheating and corrosion, compatible with rubber parts.

#### BENEFITS:

- Prevents engine overheating and freezing;
- Effectively lubricates functional surface;
- Cleans and restores cooling channels;
- Protects against chemical corrosion;
- Extends the service life of the cooling system.

#### TYPICAL CHARACTERISTICS:

Density at 20°C, g/cm <sup>3</sup>	1,060
Corrosive effect on metals, g/v2 day stands	
Pour point, °C	-39

Packing	Vendor code	Barcode
Canister plastic 10kg	020811	
Canister plastic 9l	018969	482007024024
Canister plastic 1l	018524	482007024218
Barrel metal 200l	017678	482007024050
Canister plastic 20l	017665	482007024665
Canister plastic 5l	017383	482007024219

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.