

YUKO TRANSFORMER OIL T-1500

TRANSFORMER OIL.

DESCRIPTION:

Intended for filling of power and measuring transformers, oil breaks, reactor facilities and other high-voltage equipment as main electrical insulators, including the function of arc-extinguishing medium.
Produced of sulphurous paraffin base oils, using solvent-refined and hydrogenation procedures. Used for energized insulation and transformer units, heat removal and moisture protection.

BENEFITS:

- Improved oxidation stability;
- Capability of oil to maintain the parameters at continuous operation;
- High dielectric strength.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 50°C, mm ² /s	7.9
Flash point in open crucible, °C	145
Acid index, mg KOH/g	0.005
Loss tangent of a dielectric at 90°C, %	0.5
Pour point, °C	-45

Packing	Vendor code	Barcode
Barrel metal 200l	000528	482007024118

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.