

## TURBOSYNT DIESEL 10W-40

### SEMI-SYNTHETIC MOTOR OIL FOR DIESEL ENGINES.

#### SPECIFICATIONS:

SAE 10W-40    API CH-4    API SL    ACEA E2    ACEA E5

#### DESCRIPTION:

Intended for modern air and turbo diesel engines of passenger cars, vans and trucks and other commercial vehicles. Produced of high-quality foreign base oils with additives, providing optimum performance throughout the service life.

#### CONFORMITY:

MB 228.1    MAN M271    Volvo VDS/VDS-2

#### BENEFITS:

- Consistently high performance in various operating modes;
- Optimum lubricating properties and detergency;
- Easy cold start in winter;
- Prevents high and low temperature deposits formation in the engine;
- Reliable wear protection of engine parts throughout the service life;
- Compatible with all engine sealings;

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	13,7
Density at 20°C, kg/m <sup>3</sup>	880
Viscosity index	152
Alkalinity, mg KOH/g	9,3
Flash point in open crucible, °C	218
Pour point, °C	-39

Packing	Vendor code	Barcode
Canister plastic 20l	021334	4820070247367
Canister plastic 5l	006084	482007024205
Canister plastic 1l	006083	482007024204

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.