

VDL 100 (ISO 100)

ALL-SEASON EASY-FLOWING COMPRESSOR OIL.

SPECIFICATIONS:

ISO 100

DESCRIPTION:

All-season easy-flowing compressor oil. Intended for lubricating industrial and transport compressor equipment.

Provides optimum pressure in compressor lubrication system and maximum protection in the most severe operating conditions.

It is used in mobile and stationary compressors (piston and rotary), blowers, circulating bearing systems (sliding, rolling) of production equipment operating at high temperatures.

Produced from high quality base oil with modern additive package, which guarantees a long service life of the unit.

BENEFITS:

- anti foam and water separating properties;
- provides fast oil supply and good starting properties;
- excellent lubricating ability within a wide range of temperature;
- high aging resistance and scoring protection;
- good anti corrosion properties;
- provides optimal system pressure;
- low tendency to coking property.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 40°C, mm ² /s	100
Viscosity index	90
Density at 20°C, kg/m ³	880
Flash point in open crucible, °C	225
Pour point, °C	-30

Packing	Vendor code	Barcode
Canister plastic 1l	011799	482007024530

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.