

## VEGA SYNT 10W-40

### SEMISYNTHETIC HIGH-QUALITY HYDROCRACKING MOTOR OIL.

#### SPECIFICATIONS:

SAE 10W-40    API SL    API CF    ACEA A3/B4

#### DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars and vans (injector, multivalve, turbocharged, including fitted with exhaust fumes catalysts).

Produced according to hydrocracking technology of high-quality base oils with active additives package providing stable performance. Effectively prevents carbon and lacquer formation.

#### CONFORMITY:

VW 502.00/505.00    MB 229.3    PSA B71 2300    BMW Special

#### BENEFITS:

- Reliable engine lubrication at any temperatures;
- Easy cold start at sub-zero temperatures;
- Due to the high content of synthetic components, the oil provides improved engine cleanliness;
- No high and low temperature deposits in the engine;
- Low volatility at high operating temperatures;
- A wide range of packaging meets the requirements of any equipment;

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	13.7
Density at 20°C, kg/m <sup>3</sup>	877
Viscosity index	152
TBN mg KOH/g	9.6
Flash point in open crucible, °C	218
Pour point, °C	-33

Packing	Vendor code	Barcode
Canister plastic 20l	021314	4820070241648
Barrel metal 200l	004786	482007024025
Canister plastic 5l	004871	482007024212
Canister plastic 4l	004487	482007024122
Canister plastic 1l	004489	482007024121

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.